#### Hanwha Corporation ▶▶▶ Propelling Charges

#### **Propelling Charge,** 105mm, KM67

Propelling charge KM67 is designed to use with 105mm HE, Illum. and WP projectiles.

Separate loading, white bag Type

**Propellant** KM1 Weight (full charge) 1.278kg Length

Muzzle velocity (full charge) 464.8m/sec. **Chamber pressure** 31,200 ~ 39,000psi Maximum range 11,270m (M1 HE)

Used with (Projectile) 105mm M1(HE),

M314A3(Illum.), M60(WP) etc.

105mm HOW M49, M2A1, **Used with (Cannon)** 

M2A2, M103, M137 etc.

Packing 34 charges in steel drum

58kg **Packing Drum** U.N. Number 0242 IMDG code 1.3C



### **Propelling Charge,** 155mm, KM4A2

Propelling charge KM4A2 is designed to use in 155mm howitzers for firing in Zones 3, 4, 5, 6 and 7.

Separate loading, white bag Type

**Propellant** KM1 Weight (full charge) 6.35kg Length 533.4mm Muzzle velocity (full charge) 564 m/sec. 40,500psi Max. **Chamber pressure** Maximum range 14,600m

Used with (Projectile) 155mm M107(HE), M485A2(Illum.), KM549A1(HE-RAP)

Used with (Cannon) 155mm HOW M1A1, M45, M126, M185, M198

**Packing** 1 charge in metal container

**Packing Drum** 14kg U.N. Number 0242 IMDG code 1.3C





## Propelling Charge, 155mm, KM119A1

This propelling charge is designated Zone 8 and extends the range of 155mm Howitzer M109A1, M109A2/A3, and M198.

**Type** Separate loading, white bag

PropellantKM6Weight (full charge)10.4kgLength660mmMuzzle velocity (full charge)684m/sec.Chamber pressure33,000psi Max.Maximum range18,000m

**Used with (Projectile)** 155mm M107(HE), M485A2(Illum.), KM549A1(HE-RAP)

Used with (Cannon) 155mm HOW M109, M185, M198

Packing 1 charge in metal container

 Packing Drum
 31.8kg

 U.N. Number
 0242

 IMDG code
 1.3C





# Propelling Charge, 155mm, KM203

The KM203 is a Zone 8S charge designed to supplement the standard KM3, KM4, and KM119 series charges and to provide extended range for the 155mm Howitzer M198.

**Type** Separate loading, red bag

PropellantKM30A1Weight (full charge)11.8kgLength768mmMuzzle velocity (full charge)826m/sec.Chamber pressure47,500psi Max.Maximum range30,000m

**Used with (Projectile)** 155mm KM549A1(HE-RAP), K307(BB HE)

Used with (Cannon)155mm HOW M198Packing1 charge in metal container

Packing Drum 21kg
U.N. Number 0242
IMDG code 1.3C



